

239

United States of America

FEDERAL COMMUNICATIONS COMMISSION

FM BROADCAST STATION CONSTRUCTION PERMIT



Official Mailing Address:

CAPROCK EDUCATIONAL B/CNG FOUNDATION
3515 GOODFELLOW LANE
AMARILLO, TX 79121

Authorizing Official:

Deborah G. Price

Deborah Price
Supr Applications Examiner, FM Branch
Audio Services Division
Mass Media Bureau

Grant Date: October 16, 1987

Call sign: KAMY

This permit expires 3:00 am.
local time: April 16, 1989

Permit File No.: BPED-840626IE

This authorization re-issued to reflect a call sign change from KCEI to KAMY effective 4/08/88.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

This permit shall be automatically forfeited if the station is not ready for operation within the time specified (date of expiration) or within such further time as the Commission may allow, unless completion of the station is prevented by causes not under the control of the permittee. See Sections 73.3598, 73.3599 and 73.3534 of the Commission's Rules.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of permittee:

CAPROCK EDUCATIONAL BROADCASTING FOUNDATION

Station Location:

TX-LUBBOCK

Frequency (MHz): 90.1

Call sign: KAMY

Permit No.: BPED-840626IE

Channel: 211

Class: A

Hours of Operation: Unlimited

Transmitter location (address or description):

58TH & QUIRT AVE., LUBBOCK, TX

Transmitter: Type accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: (directional or non-directional): Non-directional

Antenna coordinates: North Latitude: 33 32 31.0
West Longitude: 101 49 9.0

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the horizontal plane (kW) :	0.64	0.64
Height of radiation center above ground (meters) :	85.0	85.0
Height of radiation center above mean sea level (meters) :	1051.0	1051.0
Height of radiation center above average terrain (meters) :	82.0	82.0
Overall height of antenna structure above ground (including obstruction lighting, if any) :	91.0 meters	

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

Paragraph 1.0, FCC Form 715 (March 1978):

Antenna structures shall be painted throughout their height with alternate bands of aviation surface orange and white, terminating with aviation surface orange bands at both top and bottom. The width of the bands shall be equal and approximately one-seventh the height of the structure, provided however, that the bands shall not be more than 100 feet nor less than 1 and 1/2 feet in width. All towers shall be cleaned and repainted as often as necessary to maintain good visibility.

Paragraph 3.0, FCC Form 715 (March 1978):

There shall be installed at the top of the structure one 300 m/m electric code beacon equipped with two 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. Where a rod or other construction of not more than 20 feet in height and incapable of supporting this beacon is mounted on top of the structure and it is determined that this additional construction does not permit unobstructed visibility of the code beacon from aircraft at any normal angle of approach, there shall be installed two such beacons positioned so as to insure unobstructed visibility of at least one of the beacons from aircraft at any normal angle of approach. The beacons shall be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.

Paragraph 11.0, FCC Form 715 (March 1978):

At the approximate mid point of the over-all height of the tower there shall be installed at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes. Each light shall be mounted so as to insure unobstructed visibility of a least one light at each level from aircraft at any normal angle of approach.

Call sign: KAMY

Permit No.: BPED-840626IE

Paragraph 21.0, FCC Form 715 (March 1978):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.