

EX PARTE OR LATE FILED

PIPER & MARBURY

1200 NINETEENTH STREET, N.W.
WASHINGTON, D.C. 20036-2430
202-861-3900
FAX: 202-223-2085

DOCKET FILE COPY ORIGINAL

BALTIMORE
NEW YORK
PHILADELPHIA
LONDON
EASTON, MD

WRITER'S DIRECT DIAL
202-861-6471

October 7, 1994

HAND DELIVER

William F. Caton
Acting Secretary
Federal Communications Commission
1919 M Street, Room 222
Washington, D.C. 20554

RECEIVED
OCT 7 1994
FEDERAL COMMUNICATIONS COMMISSION
OFFICE OF SECRETARY


Re: GEN Docket No. 90-314
Correction to October 5, 1994 Ex Parte Presentation

Dear Mr. Caton:

This letter is to correct a procedural defect in the October 5, 1994 written ex parte presentation which I submitted on October 5, 1994 on behalf of Omnipoint Corporation in the above-referenced docket. This correction is not to alter or amend any of the substance of the written submission; this correction is only to include the statement that "two copies of the same have been submitted to the Commission's Secretary's Office," in full compliance with the Commission's rules. Attached is the corrected October 5 written ex parte presentation.

I am submitting to you today an original and two copies of this letter and the corrected attachment.

Sincerely,


Mark J. Connor

Enclosure

cc (w/enclosure):
Julius Knapp, OET

No. of Copies rec'd 022
List ABCDE

OMNIPOINT CORPORATION

GEN Docket No. 90-314

Ex Parte Presentation

October 5, 1994

Two copies of the same have been submitted
to the Commission's Secretary's Office

RECEIVED

OCT 7 1994

FEDERAL COMMUNICATIONS COMMISSION
OFFICE OF SECRETARY

24.238 Emission Limits:

(a) The fundamental emission of the transmitter shall be located as close to the edge of the licensee band as the transmitter is designed to operate. Compliance with the Out of Band Emission Limits is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth of 10 kHz. Out of Band Emissions shall be attenuated below 2 Watts (0dB reference) as follows: 30 dB at the licensee band edges linearly decreasing to 50 dB at 1.25 MHz above or below the licensee band; 50 dB at 1.25 MHz above or below the licensee band linearly decreasing to 60 dB at 2.50 MHz above or below the licensee band. Compliance with the Spurious Emissions Limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz. Spurious Emissions outside a licensee frequency block shall be attenuated below the transmitter power in Watts (P) by at least $43 + 10\log_{10}(P)$ decibels, or 80 decibels, whichever is the lesser attenuation.

(b) When an emission outside of the licensee frequency block causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.