

Eric Wagner
Director
Federal Regulatory Affairs



1300 I Street, NW
Suite 400 West
Washington, DC 20005
(202) 515-2501
(202) 336-7922 (fax)
eric.wagner@verizon.com

March 29, 2010

Marlene H. Dortch
Secretary
Federal Communications Commission
445 12th Street, SW
Washington, DC 20554

FILED/ACCEPTED

MAR 29 2010

Federal Communications Commission
Office of the Secretary

Re: CC Docket Nos. 88-2 and 96-128

Dear Ms. Dortch:

Attached is the 2010 Verizon East Annual FCC Open Network Architecture (ONA) report, reflecting ONA implementations and future plans.

Please contact me should you have any questions.

Very truly yours,

A handwritten signature in black ink, appearing to read "E. Wagner".

Attachment

Eric Wagner
Director
Federal Regulatory Affairs



1300 I Street, NW
Suite 400 West
Washington, DC 20005
(202) 515-2501
(202) 336-7922 (fax)
eric.wagner@verizon.com

March 29, 2010

FILED/ACCEPTED

MAR 29 2010

Marlene H. Dortch
Secretary
Federal Communications Commission
445 12th Street, SW
Washington, DC 20554

Federal Communications Commission
Office of the Secretary

Re: GTE Open Network Architecture, CC Docket No. 92-256
Phase I; Installation and Maintenance Non Discrimination Reports CC Docket No. 88-2,
Implementation of Pay Telephone Reclassification and Compensation Provisions of the Telecommunications Act of 1996, CC Docket No. 96-128

Dear Ms. Dortch:

Attached is the Phase I Semiannual 2010 ONA Nondiscriminatory Reports for Verizon being filed pursuant FCC Orders in the above-styled dockets.

Please contact me should you have any questions.

Very truly yours,

A handwritten signature in black ink that reads "Eric Wagner".

Attachment

Eric Wagner
Director
Federal Regulatory Affairs



DOCKET

1300 I Street, NW
Suite 400 West
Washington, DC 20005
(202) 515-2501
(202) 336-7922 (fax)
eric.wagner@verizon.com

March 29, 2010

Marlene H. Dortch
Secretary
Federal Communications Commission
445 12th Street, SW
Washington, DC 20554

FILED/AC...
MAR 29 2010
Federal Communications Commission
Office of the Secretary

**Re: GTE Open Network Architecture, CC Docket No. 92-256
Phase I; Installation and Maintenance Non Discrimination Reports CC Docket No. 88-2,
Implementation of Pay Telephone Reclassification and Compensation Provisions of
the Telecommunications Act of 1996, CC Docket No. 96-128**

Dear Ms. Dortch:

Attached is the Phase 1 Semiannual 2010 ONA Nondiscriminatory Reports for Verizon being filed pursuant FCC Orders in the above-styled dockets.

Please contact me should you have any questions.

Very truly yours,

Attachment

No. of Copies rec'd 0
List ABCDE

MARCH Semi Annual fGTE Package to FCC

CD

MARCH 2010 GTE'S DEPLOYMENT OF ONA SERVICES.DOC
MARCH 2010 fGTE svc desc.doc
MARCH 2010 gte Relationship REPORT .doc
MARCH 2010 fgte tariff ref all states all products report.doc
MARCH 2010 fgte cons tariff ref matrix.xls
MARCH 2010 Abbreviation KEY.DOC

Paper Reports:

Consolidated Tariff Reference Matrix (fGTE)

MARCH 2010 fgte cons tariff ref matrix.xls

Consolidated Tariff Reference Matrix

03/01/10	Generic Name of Service																		
Page	Abbreviated Name	Code	AZ	CA	FL	ID	IL	IN	MI	NV	NC	OH	OR	PA	SC	TX	VA	WA	WI
101	Acc To Cir Ch Transmissn	1026	B	BB	BB	BB	BB	BB	BB	B	BB	BB	BB	BB	BB	BB	B	B	BB
34	Alternate Routing	1041	B	BB	BB	BB	BB	BB		B	BB	BB	BB	BB	BB	BB	B	B	BB
114	Anonymous Call Block	9011		C	C	C	C	C	C	C	C	C	C	C	C	C			C
102	Automatic Protect Swtchg	1028	BB	BB	BB	BB	B	BB	BB	BB	BB	BB	BB	B	BB	BB	B	B	BB
36	Automatic Recall	1044		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
104	Bridging	1029	BB	B	B	BB													
116	Busy Redial	9001		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
6	C1 Typ A - Ckt Sw Line	1039	A	AA	AA	AA	AA	AA	AA	A	A	AA	AA	AA	AA	AA	A	A	AA
8	C1 Typ B - Ckt Sw Trunk	1040	A	AA	AA	AA	AA	AA	AA	A	A	AA	AA	AA	AA	AA	A	A	AA
11	C2 Typ A - X.25 Pkt Sw	1001		A	A		A	A				A	A						
13	C2 Typ B - X.75 Pkt Sw	1002		AA	AA		AA	AA			A	AA	AA	A		A	A	A	
15	C3 Typ C - Ded Voice Grd	1017	AA	A	AA	AA	AA	AA	AA	AA	A	A	AA						
17	C3 Typ D - Ded Prgm Audio	1018	AA	A	AA	AA	AA	AA	AA	AA	A	A	AA						
19	C3 Typ E - Ded Video	1019	A	AA	AA	AA	AA	AA	AA	A	AA	AA	AA	A	AA	AA	A	A	AA
21	C3 Typ F - Ded <64kbps	1020	AA	A	A	AA													
23	C3 Typ G - Ded 1.544Mbps	1021	AA	A	AA	AA	A	A	AA										
25	C3 Typ H - Ded >1.544Mbps	1022	AA	A	AA	AA	A	A	AA										
27	C3 Typ I - Ded Alrt Trnsp	1023	A	AA	AA	A	AA	AA	AA	A	A	AA	AA	A	AA	A	A	A	AA
29	C3 Typ K - Ded 64 kbps	1037		AA	AA	AA	AA	AA	AA	A	AA	AA	AA	AA	AA	AA	A	A	AA
31	C4 - Ded Ntwk Accss Link	1025	A	AA	A	A	AA	AA	AA	A	A	AA	AA	AA	AA	AA	A	A	AA
118	CF Fixed	9007	C	C	C	C	C	C		C	C	C	C	C		C	C	C	C
51	CF Mult Sim Call Intersw	1052			C						C		C		C	C	C	C	C
54	CF Var Act w/o Crtsy Cal	1054		C			C	C		C		C					C	C	
55	CF Var Remote Act/Cntrol	1055		C						C							C	C	
52	CF Variable	1053		C	C	C	C	C	C	C		C					C	C	C
41	CFBL Interswitch	1047		C	B	C	C	C		C	B	C	C	C	C	C	C	C	C
39	CFBL Intraswitch	1046		C	B	C	C	C	C	C		C	C	C	C	C	C	C	C
43	CFBL/DA Cust Act/Deact	1048		C			C	C	C			C		C			C	C	C
45	CFBL/DA Cust Fwd To No.	1049		C			C	C				C		C			C	C	C
117	CFBL/DA Fixed	9008	C	C	B		C	C	C		B	C	C	C	B	C	C	C	C
49	CFDA Interswitch	1051		C	B	C	C	C		C	B	C	C	C		C	C	C	C
47	CFDA Intraswitch	1050		C	B	C	C	C	C	C		C	C	C	B	C	C	C	C
98	Call Det Recd'g Rpts Pkt	1003		C			C	C									C		
119	Call Restriction Service	9017		C	C		C	C	C	C	C	C	C	C	C	C	C	C	C
120	Call Waiting	9004	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
57	Call Waiting Cancel	1056		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
59	Clld DN Deliv via DID	1057	BB																
61	Clig Blig Num Deliv FG B	1060	BB	B	B	BB													
63	Clig Blig Num Deliv FG D	1061	BB	BB	BB	BB	BB	BB	B	BB	B	BB	BB	BB	B	BB	B	B	BB
65	Clig DN Deliv via ICLID	1064		B	BB	BB	B		BB	BB	C	BB	BB	B	BB	B	B	B	BB
105	Conditioning	1030	BB	B	B	BB													
122	Cust Controllable Ring	9023		C	B		C	C	B	C	B	C		C	C	C	C	C	C
69	Cust Originated Trace	1066		C	C	C	C		C	C	C	C	C	C	C	C	C	C	C

Consolidated Tariff Reference Matrix

Page	Generic Name of Service Abbreviated Name	Code	AZ	CA	FL	ID	IL	IN	MI	NV	NC	OH	OR	PA	SC	TX	VA	WA	WI
67	Cxr Select On Rvrs Chrg	1065	BB	B	BB	BB	B	B	BB										
103	Data Over Voice (DOV)	1031		B									B		B	BB		B	
107	Derived Ch (Monitoring)	1032			C														
74	Dist Ring Term Screen	1069		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
71	Distinctive Ringing	1068		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
131	Do Not Disturb	9010		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
99	Fast Select Accept Pkt	1007		BB	BB		BB	BB			B	BB	BB	BB	B	B	B	B	
100	Fast Select Request Pkt	1008		BB	BB		BB	BB			B	BB	BB	BB		B	B	B	
123	GTE® Dial DataLink	9021					C	C	B				B		B		C	C	C
136	High Cap Dig Handoff Svc	9024	B	BB	BB	BB	BB	BB	BB	B	BB	BB	BB	B	BB	BB	B	B	BB
76	Hot Line	1070					C	C	C		C			C	C	C			C
130	Inband Signaling	9015	BB	B	B	BB													
124	Last Number Redial	9003		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
82	MLHG UCD Line Hunting	1081	BB	B	B	BB													
84	MLHG UCD With Queuing	1082	B	BB	BB	BB	BB	BB	BB	B	BB	BB	BB	BB	BB	BB	B	B	BB
78	MWI ATR Audible Msg Wtg	1073		C	B		C	C		C	C			C	B			C	C
126	MWI ATR Audible Ring Bst	9019		C	B		C	C	B		B	C		C	C			C	C
137	MWI Activation (ARB)	9022		BB	B		B												
112	MWI Activation (Audible)	1075	B	BB	B		B	B	B	BB	B	B			B	B	B		
125	MegaConnect (SMDS)	9020		BB	B		B				B		B	B		B	BB		
110	Message Desk (SMDI)	1072	B	BB	BB	B	BB	BB	BB	B	B	BB	B	B	BB	BB	B	B	BB
80	Multiline Hunt Group	1077	BB	B	B	BB													
127	Multiplexing-Digital	9014	BB	B	B	BB													
138	Premier Msg Svc Interf	9028	B	B	B		B	B	B	B	BB	B	B	B	B	B	B	B	B
135	Priority Packet	9018		B	B		BB	BB			B	BB	B		B	B	B	B	B
128	Remote Call Forwarding	9008	BB	B	BB	BB													
108	Route Diversity	1096	BB	B	BB	BB	BB	BB	BB	BB	B	BB	BB	BB	BB	BB	B	B	BB
129	Saved Number Redial	9002		C	C		C	C	C		C	C	C	C	C	C	C	C	C
109	Secondary Ch Capability	1034		BB	B	B			BB		BB		B		BB	BB	B	B	
86	Selective Call Forward'g	1084		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
89	Selective Call Rejection	1085		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
132	Special Call Waiting	9009		C	C		C	C	C		C	C	C	C	C	C	C	C	C
92	Speed Calling	1087	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
139	SS7MWI	9025	B	B	B		B	B	BB	B	B	BB	B	B	BB	B	B	B	B
115	Third Numb Bill Inhibitd	9012	BB	B	BB	BB													
94	Three Way Call Transfer	1089	B	BB	BB	BB	BB	BB	BB	B	BB	BB	BB	BB	BB	BB	B	B	BB
133	Three Way Calling	9005	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
96	Unif 7D Acc Num RCF	1090	B	B	B				B	B	B	B			B	B			

Abbreviations:

- A=BSA
- B=BSE
- C=CNS
- D=BSE/CNS

Under each state abbreviation the left column contains FCC tariff information and the right column contains state tariff information.

MARCH Semi Annual fBA Package to FCC

CD

MARCH 2010 CONSOLIDATED svc desc.doc
MARCH 2010 CONSOLIDATED APP 1 Relationship REPORT .doc
MARCH 2010 CONSOLIDATED APP 2 CONTACTS.DOC
MARCH 2010 CONSOLIDATED APP 3 BSA MATRIX.DOC
MARCH 2010 CONSOLIDATED tariff ref matrix.xls
MARCH 2010 Abbreviation KEY.DOC
MARCH 2010 CONSOLIDATED APPs A B.doc

Paper Reports:

MARCH 2010 CONSOLIDATED svc desc.doc
MARCH 2010 CONSOLIDATED APP 1 Relationship REPORT .doc
MARCH 2010 CONSOLIDATED APP 2 CONTACTS.DOC
MARCH 2010 CONSOLIDATED APP 3 BSA MATRIX.DOC
MARCH 2010 CONSOLIDATED tariff ref matrix.xls
MARCH 2010 Abbreviation KEY.DOC
MARCH 2010 CONSOLIDATED APPs A B.doc

BELL OPERATING COMPANIES

Service Descriptions
ONA Services User Guide

January 31, 2010

ONA Services

Names, Descriptions, Cross References

FOREWORD

Attached is the Services Descriptions section of the ONA Services User Guide, an update of information that was previously issued on July 31, 2009.

The Services Descriptions section of the ONA Services User Guide represents an agreement on the part of the BOCs for uniform names and technical descriptions of the Basic Serving Arrangements (BSAs), Basic Service Elements (BSEs) and Complementary Network Services (CNSs) that relate to the ESP requests included in BOC ONA Special Report Number 1, Issue 2 (October 1987). That Special Report is a compilation of the 118 requests received by all the BOCs during the input process for ESP requests prior to filing of the 2/1/88 ONA Plans. Some items, marked with an asterisk (*) in their titles, have been deleted after the last issue of the report based on the availability of updated information indicating that they cannot be offered. For each service listed, a table is provided that gives an indication of which BOCs plan to offer the service, the individual BOC's product name, and whether the BOC classifies the service as a BSA, BSE or CNS.

The BSAs, which respond to the 118 ESP requests for ONA services, are listed in the following four categories of Basic Serving Arrangements:

- Circuit Switched Serving Arrangements

A circuit switched basic serving arrangement (BSA) provides an enhanced service provider (ESP) with a connection to the circuit switched network.

- Packet Switched Serving Arrangements

A packet switched BSA provides an ESP with a connection to the packet switched network.

- Dedicated Serving Arrangements

A dedicated BSA provides an ESP with a dedicated point-to-point connection through the network.

- Dedicated Network Access Link Serving Arrangements

A dedicated network access link (DNAL) BSA provides a dedicated data channel between the ESP's termination and a designated central office which contains the specific features required by the ESP. The DNAL is used to transmit control information from the ESP to the network or to deliver information from the network to the ESP.

Following the BSAs are the BSEs and CNSs, which are listed in alphabetical order in the above four BSA categories. These BSEs and CNSs respond to the 118 ESP requests for ONA services that were made to all BOCs. A description of each BSE or CNS is provided, which includes a brief technical description and a table listing the product name for each company that offers the service.

Appendix 1 contains a set of descriptions of ONA services that are offered by one or more BOC in response to requests received independent of the 118 ESP requests received by all BOCs. Included is a technical description and a table with the product name for each company that offers the service.

Appendix 2 contains a list of BOC contacts.

Appendix 3 contains the BSA Matrix, a report that shows the relationship between the BSAs and the BSEs included in the ONA Services User Guide. Included is a table showing the generic name for each BSA, and the specific name used by each company offering the BSA. Also included is a set of tables, one for each BSA, listing which BSEs are associated with the BSA for each company. These matrices only include generic BSAs and BSEs, and do not include the CNSs or any region specific services.

This report does not supersede any information provided in the BOC ONA plans and amendments. All capabilities described are not available in all switching or transmission systems. Generic descriptions of BSAs do not imply that applicable generic functions and capabilities are available or compatible with all types of BSAs. In addition, generic descriptions are intended for informational purposes and their existence does not imply that specific products and/or services are necessarily tariffed and/or available in any or all state/ federal jurisdictions within a particular company's service area. The BSAs, BSEs and CNSs identified in this report cannot be ordered until appropriate tariffs are effective. Some ONA services may not be tariffed in all areas. The reader should refer to the individual BOC ONA plans and amendments or the BOC contacts listed in Appendix 2 to this report for information on BOC availability and deployment plans for the technical capabilities described in this report.

References to switching system generics that have not yet been released by the vendors are based on our current information about which features are planned for inclusion in those generic releases. If the vendors change the availability of any features for future generic releases that are referenced in this document, the availability of some services may be affected.

Technical references that are publicly available are listed for each service, where available. Ordering information for each of the technical references may be found in the *Telcordia Technologies Catalog of Technical Information* (including ordering information for reference documents published by individual regional companies). To order, call 1-866-672-6997 toll free from anywhere in the USA; call (732) 699-6700 for foreign calls; fax (732) 336-2226.

Recently, various BOCs have completed, or are in the process of completing, corporate mergers. For this document, the old company names will continue to be used (for example, Bell Atlantic and NYNEX are listed separately, rather than being combined under the Verizon name; Southwestern Bell and Pacific Bell and Ameritech and BellSouth are listed separately, rather than being combined under the AT&T name).

Questions on this report should be directed to the BOC contacts listed in Appendix 2 to this report.

BSA Descriptions	6
1. <i>Category 1 - Circuit Switched BSA</i>	7
1.1 Category 1, Type A - Circuit Switched Line BSA (1039)	7
1.2 Category 1, Type B - Circuit Switched Trunk BSA (1040)	9
2. <i>Category 2 - Packet Switched Basic Serving Arrangement.....</i>	12
2.1 Category 2, Type A - X.25 Packet Switched BSA (1001).....	12
2.2 Category 2, Type B - X.75 Packet Switched BSA (1002).....	15
3. <i>Category 3 - Dedicated Basic Serving Arrangement</i>	18
3.1 Category 3, Type A - Dedicated Metallic BSA (1015).....	18
3.2 Category 3, Type B - Dedicated Telegraph BSA (1016)	20
3.3 Category 3, Type C - Dedicated Voice Grade BSA (1017)	22
3.4 Category 3, Type D - Dedicated Program Audio BSA (1018)	24
3.5 Category 3, Type E - Dedicated Video BSA (1019).....	26
3.6 Category 3, Type F - Dedicated Digital (< 64 kbps) BSA (1020)	28
3.7 Category 3, Type G - Dedicated High Capacity Digital (1.544 Mbps) BSA (1021).....	30
3.8 Category 3, Type H - Dedicated High Capacity Digital (>1.544 Mbps) BSA (1022).....	32
3.9 Category 3, Type I - Dedicated Alert Transport BSA (1023).....	34
3.10 Category 3, Type J - Dedicated Derived Channel BSA (1024).....	36
3.11 Category 3, Type K - Dedicated Digital (64 Kbps) BSA (1037)	38
4. <i>Category 4 - Dedicated Network Access Link BSA (1025).....</i>	40
BSE and CNS Descriptions	42
1. <i>Technical Descriptions for Circuit Switched Serving Arrangements</i>	43
Alternate Routing (1041)	43
Answer Supervision With A Line Side Interface (1042)	45
Automatic Callback (1043).....	47
Automatic Recall (1044).....	49
Call Detail Recording Reports (1045).....	52
Call Forwarding - Busy Line Intraswitch (1046).....	54
Call Forwarding - Busy Line Interswitch (1047).....	56
Call Forwarding - Busy Line or Don't Answer - Customer Control of Activation/Deactivation (1048).....	58
Call Forwarding - Busy Line or Don't Answer - Customer Control of Forward-To Number (1049).....	60
Call Forwarding Don't Answer After Call Waiting (CFDA After CW) (1093).....	62
Call Forwarding - Don't Answer Intraswitch (1050)	64
Call Forwarding - Don't Answer Interswitch (1051)	66
Call Forwarding - Multiple Simultaneous Calls Interswitch (1052).....	68
Call Forwarding - Variable (1053)	69
Call Forwarding - Variable - Activation Without Courtesy Call (1054).....	71
Call Forwarding - Variable - Remote Activation/Control (1055).....	73
Call Forwarding With Variable Rings (1102).....	75
Call Waiting - Cancel (1056)	76
Called Directory Number Delivery via DID (1057)	78
Called Directory Number Delivery via 900NXX (1059).....	80
Calling Billing Number Delivery - FG B Protocol (1060)	81
Calling Billing Number Delivery - FG D Protocol (1061).....	83
Calling Directory Number Delivery - via ICLID (1064)	85
Carrier Selection On Reverse Charge (1065)	87
Coin Phone With Post Dialing Tone Capability (1062).....	89

Customer Originated Trace (1066)	90
Cut Off On Disconnect (1095)	92
DID Trunk Queuing (1067)	93
Distinctive Ringing (1068)	94
Distinctive Ringing - Terminating Screening (1069)	97
Faster Signaling On DID (1094)	99
Flexible ANI Information Digits (1058)	100
Hot Line (1070)	101
Message Waiting Indicator (MWI) - Ability To Receive Audible Message Waiting (1073)	102
Message Waiting Indicator (MWI) - Ability to Receive Visual Message Waiting(1074)	104
Multiline Hunt Group (1077)	105
Multiline Hunt Group - C. O. Announcements (1078)	107
Multiline Hunt Group - Individual Access To Each Port In Hunt Group (1079)	109
Multiline Hunt Group - Overflow (1080)	111
Multiline Hunt Group - Uniform Call Distribution Line Hunting (1081)	113
Multiline Hunt Group - UCD With Queuing (1082)	115
Name of Calling Party (1097)	117
Reverse Billing On Circuit Switched Access (1083)	119
Selective Call Forwarding (1084)	120
Selective Call Rejection (1085)	123
Shared Speed Calling (1086)	126
Single Number Access For Multiple Locations (1098)	128
Speed Calling (1087)	130
Tandem Routing (1088)	132
Three Way Call Transfer (1089)	134
Uniform 7 Digit Access Number - Remote Call Forwarding (1090)	136
Uniform 7 Digit Access Number via Overlay Networking (1091)	138
Warm Line (1092)	139
2. Technical Descriptions for Packet Switched Serving Arrangements	141
Call Detail Recording Reports (Packet) (1003)	141
Call Redirection - Packet (1004)	142
Closed User Groups - Packet (1005)	143
Direct Call - Packet (1006)	145
Fast Select Acceptance - Packet (1007)	146
Fast Select Request - Packet (1008)	147
Hunt Groups - Packet (1009)	148
Menu Access Translator - Gateway (1010)	149
Message Waiting Indicator - Packet Access (1011)	150
Preselection for Data Services (1013)	151
Reverse Charge Acceptance - Packet (1014)	152
3. Technical Descriptions for Dedicated Access Arrangements	153
Access To Clear Channel Transmission (1026)	153
Access To Operations Support Systems Information (1027)	154
Automatic Protection Switching (1028)	155
Bridging (1029)	157
Conditioning (1030)	159
Data Over Voice (DOV) Service (1031)	160
Derived Channels (Monitoring) (1032)	162
Extended Superframe Conditioning (1033)	164
Route Diversity (1096)	165
Secondary Channel Capability (1034)	166
Statistical Multiplexer (1035)	168
Verify Integrity of Subscriber Lines (1036)	169
4. Technical Descriptions for Dedicated Network Access Link Serving Arrangements	171
Calling Directory Number Delivery - via BCLID (1063)	171

Make Busy Key (1071)	173
Message Desk (SMDI) (1072)	175
Message Desk (SMDI) - Expanded (1099)	177
Message Waiting Indicator - Activation (Audible) (1075)	179
Message Waiting Indicator Activation (Audible) - Expanded (1100)	181
Message Waiting Indicator - Activation (Visual) (1076)	183
Message Waiting Indicator Activation (Visual) - Expanded (1101)	184
Network Reconfiguration (1038)	186

BSA Descriptions

BSAs have been arranged into four categories:

1. Circuit Switched
2. Packet Switched
3. Dedicated
4. Dedicated Network Access Link

Each category may have several types. Following are descriptions of the BSA categories and the associated BSA types.

1. Category 1 - Circuit Switched BSA

A circuit switched basic serving arrangement (BSA) provides an enhanced serviceprovider (ESP) with a connection to the circuit switched network. This BSA is capable of supporting analog signals of approximately 300 to 3000 Hz or a circuit switched digital interface with a call type of digital encoded voice, 3.1 kHz or 7 kHz audio, 56 kbps or 64 kbps data transmission. This BSA may also transmit voice grade analog data. The transmission interface may be 2-wire or 4-wire, or derived from a variety of multiplexing alternatives (for example, Digital Signal (DS) level 0 from DS level 1, or DS1 from DS3).

This BSA may support one-way or two-way directionality. Calls are set up and taken down on a call by call basis. The transport/usage element could be intra-office or inter-office.

Route diversity may be available with this serving arrangement.

1.1 Category 1, Type A - Circuit Switched Line BSA (1039)

Service Description

A circuit switched line BSA provides an ESP with a line side connection to the circuit switched network.


This line side connection could include alternative types of network connection, address and supervisory in-band or out-of-band signaling. Examples of network connections are standard telephone line or a line side type connection (e.g., PBX service). This BSA may support one-way or two-way directionality on a 2-wire or 4-wire transmission interface.

Calls are set up and taken down on a call by call basis. The calling scope may include, for example, an entire Local Access and Transport Area (LATA), a market area or be limited to all or part of a metropolitan area. Directory numbers are assigned from the North American Numbering Plan without any special routing or other use of the number.

Generic Name of BSA	Regional Company BSA Name
Category 1, Type A - Circuit Switched Line BSA*	AM - Circuit Switched Line
	BA - Business Individual Line
	BA - Line Side BSA - FX (3021)
	BA - Line Side BSA - IC (3022)
	BS - Voice Grade - Line - Circuit Switched
	NX - Circuit Switched - Line
	PB - Access Line Arrangement
	SWB - Circuit Switched - Line Side Basic Serving Arrangement (BSA-A)
Qwest - Voice Grade - Line - Circuit Switched	

* Based on the Federal Communications Commission (FCC) CC Docket 89-79 Order dated July 11, 1991, there will be a new line side BSA on FCC approval of tariffs submitted November 1, 1991.

Voice Grade – Line – Circuit Switched – BSA



Alternatives

An alternative is an item that must be selected for the BSA to be technically meaningful. Alternative items may be available from some or all of the Local Exchange Carriers (LECs). Refer to the individual LEC tariff reference diskette for the reference information where LEC defined alternatives may be found. Examples of potential alternatives may be: Service Code Denial and Uniform Call Distribution.

Signaling

Signaling arrangements extend line circuit or signaling circuit alerting information on metallic or fiber facilities from one customer premises location to another customer premises location. The signaling arrangement can be terminated on trunk-like or line side interfaces of the LEC switch. Examples of address signaling on an analog interface are dial pulse or dual tone multifrequency (DTMF) with supervisory signaling of loop start or ground start. A digital interface will offer address and supervisory signaling via an out-of-band standardized protocol.

Transmission

The subject of transmission covers a broad range of performance considerations related to the physical facilities that compose network architecture. Transmission parameters are designed to provide objective transmission performance characteristics, as perceived by the end user and LEC, between the points of termination. Transmission parameters are defined for each Network Interface (see below) supporting this BSA. These parameters are defined in the reference documentation.

Network Interfaces

The electrical and physical interface with the LEC is described by a Network Channel Interface (NCI) code for each end user termination and each service provider termination. NCI codes are provided to aid the user in understanding the relationship of the network interface to the electrical or optical characteristics of the interface. NCI codes have four basic components: (1) number of conductors (wire or fibers), (2) protocol code, (3) nominal reference impedance code, and (4) any applicable protocol options.

References

- GR-334 Switched Access Service: Transmission Parameter Limits and Interface Combinations, Issue 1, July 1994
- Qwest's document 77316 Pacific Northwest Bell's Addendum to Voice Grade Switched Access Service TR-NPL-000334, April 1986.

1.2 Category I, Type B - Circuit Switched Trunk BSA (1040)


Service Description

A circuit switched trunk BSA provides an enhanced service provider (ESP) with a trunk side connection to the circuit switched network.

Various types of network connections, address signaling and supervisory signaling are available. An example of network connections to the serving office may be direct trunk or a tandem connection. Calls are set up and taken down on a call-by-call basis. Different access arrangements, based on the North American Numbering Plan, are available from the Local Exchange Carriers (LEC). This BSA may support one-way or two-way directionality.

Generic Name of BSA	Regional Company BSA Name
Category I, Type B - Circuit Switched Trunk BSA	AM - Circuit Switched Trunk BA – Trunkside BSA BA - Trunkside BSA - 950 Option BA - Trunkside BSA - 10XXX Option (3025) BS - Circuit Switched Trunk - Voice Grade NX - Circuit Switched Trunk PB - Access Trunk Arrangement (950) PB - Access Trunk Arrangement (10XXX) SWB - Circuit Switched - Trunk Side Alternative B Basic Serving Arrangement (BSA-B) SWB - Circuit Switched - Trunk Side Alternative D Basic Serving Arrangement (BSA-D) Qwest - Voice Grade - Trunk - Circuit Switched

Voice Grade – Trunk – Circuit Switched — BSA



Alternatives

An alternative is an item that must be selected for the BSA to be technically meaningful. Alternative items may be available from some or all of the LECs. Refer to the individual LEC tariff reference diskette for the reference information where LEC

defined alternatives may be found. Examples of potential alternatives may be: Service Class Routing, Dial Pulse Address Signaling, and Cut Through.

Signaling

Signaling arrangements extend trunk circuit or signaling circuit alerting information on metallic or fiber facilities from one customer premises location to another customer premises location. These signals are the means by which the end user initiates a request for service, holds a connection or releases a connection. The signaling arrangements can be terminated on line-like or trunk side interfaces of the LEC switch. Examples of point-of-termination supervisory signaling arrangements that may be ordered are Multi-Frequency (in-band), Signaling System 7 (SS7) (out of band), reverse battery and E&M.

Transmission

The subject of transmission covers a broad range of performance considerations related to the physical facilities that compose network architecture. Transmission parameters are designed to provide objective transmission performance characteristics, as perceived by the end user and LEC, between the points of termination. Transmission parameters are defined for each Network Interface (see below) supporting this BSA. These parameters are defined in the reference documentation.

Network Interfaces

The electrical and physical interface with the LEC is described by a Network Channel Interface (NCI) code for each end user termination and each service provider termination. NCI codes are provided to aid the user in understanding the relationship of the network interface to the electrical or optical characteristics of the interface. NCI codes have four basic components: (1) number of conductors (wire or fibers), (2) protocol code, (3) nominal reference impedance code, and (4) any applicable protocol options.

References

- GR-334 Switched Access Service: Transmission Parameter Limits and Interface Combinations, Issue 1, July 1994
- GR-698 LSSGR: Feature Group B FSD 20-24-0300, Issue 1, June 2000 (replaces TR-TSY-000698 Issue 1 and Revision 1 – no technical changes)
- LSSGR FR-64 (formerly FR-NWT-000064), GR-690, FSD 20-24-0000, Exchange Access Interconnection, Issue 1, March 1991, Issue 2, September 1995, Revision 01, November 1996
- TR-NPL-000258 Compatibility Information for Feature Group D Switched Access Service, Issue 1, October 1985.
- SR-NPL-001321 Connection Setup Time for Feature Group D and Terminating Feature Group B, Special Report, Issue 1, February 1989. [No longer listed.]
- Ameritech reference: AM TR-TMO-000094 Switched Access Service Feature Group D, August 1992. (Written as a companion document to GR-334, Switched Access Service: Transmission Parameter Limits and Interface Combinations.)

References for SS7

- GR-905 Common Channel Signaling Network Interface Specification (CCSNIS) Supporting Network Interconnection, Message Transfer Part (MTP), and ISDN User Part (ISDNUP), Issue 11 - December 2008 (replaces GR-905, Issue 10)
- GR-394 LSSGR: Switching System Generic Requirements for Interexchange Carrier Interconnection (ICI) Using the Integrated Services Digital Network User Part (ISDNUP) (A module of LSSGR FR-64), Issue 8 – November 2007 (replaces Issue 7)

References for Signaling Arrangements

- TA-NPL-000912 Compatibility Information for Telephone Exchange Service, Issue 1, February 1989. [No longer listed.]
- SR-2275 Telcordia Notes on the Networks, Issue 4, October 2000 (replaces SR-TSV-02275, Issue 3)

2. Category 2 - Packet Switched Basic Serving Arrangement

A packet switched BSA provides an ESP with a connection to the packet switched network via virtual and permanent virtual circuit connections. This BSA is capable of supporting analog or digital signals of various transmission rates. The transmission interface may be 2-wire or 4-wire, or derived from a variety of multiplexing alternatives (for example, Digital Signal (DS) level 0 from DS level 1, or DS1 from DS3).

2.1 Category 2, Type A - X.25 Packet Switched BSA (1001)

Service Description

The Type A Packet Switched BSA provides an ESP with X.25 or X.31 access to the BOC packet switching network via virtual and permanent virtual circuit connections. This interface conforms to Recommendations X.25 and X.31 of the International Telecommunication Union-Telecommunication Standardization Sector (ITU-TS) (formerly the International Telegraph and Telephone Consultative Committee [CCITT]).


X.25 includes physical, link and packet level procedures. At the physical level, data signaling rates of 1.2, 2.4, 4.8, 9.6 and 56 kbps are supported. The link level protocol supported at the interface is Link Access Protocol Balanced (LAPB). The main functions of the link level protocol are to ensure that the packets cross the Data Terminal Equipment/Data Communications Equipment (DTE/DCE) interface essentially error free and reach their destination in a correctly transmitted sequence. The network level access protocol provides the procedures required to set up, maintain and clear virtual calls. X.31 defines the recommended procedures for using Q.931 protocol to establish digital customer premises equipment (CPE) calls to a packet network in accordance with defined bearer services.

Generic Name of BSA	Regional Company BSA Name
Category 2, Type A - X.25 Packet Switched BSA	AM - Packet Switched Network Service (X.25) BA - Public Data Network: X.25 BS - PulseLink [®] Packet Switching - X.25 NX - INFOPATH [®] Packet Switching Service PB - Public Packet Switching (X.25) SWB - Packet Switched - MicroLink II SM (X.25 Version) Qwest - Packet Switching (X.25)

[®] PulseLink is a registered trademark of BellSouth.

[®] INFOPATH is a registered service mark of NYNEX.

SM MicroLink II is a registered service mark of Southwestern Bell Telephone.



Alternatives

An alternative is an item that must be selected for the BSA to be technically meaningful. Alternative items may be available from some or all of the Local Exchange Carriers (LECs). Refer to the individual LEC tariff reference diskette for the reference information where LEC defined alternatives may be found. Examples of potential alternatives may be: Logical Channel, Flow Control Parameters, and Multiple Network Addresses.

Signaling

Signaling arrangements extend alerting information on metallic or fiber facilities from one customer premises location to another customer premises location. Dial (circuit-switched) access provides low- to moderate-throughput Public Packet Switched Network (PPSN) access through the voice telephone network. With dial-in access, a customer terminal and modem are attached to the Public Switched Telephone Network (PSTN) loop. The customer dials a North American Numbering Plan (NANP) address and the PSTN routes the call to a PPSN dial-up port. The PPSN answers the call with a modem supporting one of several modem protocols.

With dial-out access, a call is routed to a PPSN interface supporting dial-out service. At this interface, the access concentrator obtains the NANP address and uses the ITU-TS (formerly CCITT) V.25 calling procedures to instruct the PPSN modem to establish a physical connection with the customer via the PSTN.

Dedicated (nonswitched) access provides the customer with continuously available interfaces to the PPSN.

Transmission

The subject of transmission covers a broad range of performance considerations related to the physical facilities that compose network architecture. Transmission parameters are designed to provide objective transmission performance characteristics, as perceived by the end user and LEC, between the points of termination. Transmission parameters are defined for each Network Interface (see below) supporting this BSA. These parameters are defined in the reference documentation.

Network Interfaces

The electrical and physical interface with the LEC is described by a Network Channel Interface (NCI) code for each end user termination and each service provider termination. NCI codes are provided to aid the user in understanding the relationship of the network interface to the electrical or optical characteristics of the interface. NCI codes have four basic components: (1) number of conductors (wire or fibers), (2) protocol code, (3) nominal reference impedance code, and (4) any applicable protocol options.

References

- GR-301 Public Packet Switched Network Generic Requirements (PPSNGR) (replaces TR-TSY-301, Issue 2), Issue 2, December 1997

- TR-NPL-000011 Asynchronous Terminal and Host Interface Reference, Issue 1, March 1985[No longer listed.]
- Ameritech TR-NPL-000001 Public Packet Services Technical Interface Specifications, Issue 2, September 1988
- Ameritech TR-NPL-000002 Technical Interface Specifications for X.25 Service. Issue 2, May 1988
- Ameritech TR-NPL-000003 Technical Interface Specifications for Asynchronous Service, Issue 2, May 1988
- Ameritech TR-NPL-000007 Digital Service Interface Specifications, Type 1, Issue B, December 1988
- Bell Atlantic TR 72211 Interface Specification For The Bell Atlantic Public Data Network, Issue C, December 1991
- BellSouth TR-73513 PulseLink[®] X.25 Interface Specification, Issue A, June 1987
- BellSouth TR-73516 PulseLink[®] Physical Interface Specification, Issue C. September 1991
- NYNEX NTR-74250 INFOPATH[®] Packet Switching Service X.25 Interface Specification, Issue 2, January 1988
- NYNEX NTR-74252 INFOPATH[®] Packet Switching Service Asynchronous Interface Specification, Issue 2 January 1988
- Pacific Bell PUB L-780060-PB Public Packet Switching (PPS) - Technical Interface Specification, Issue 1, August 1989
- Southwestern Bell Telephone Technical Publication TP 76800, MicroLink IISM X.25/X.75 Reference, Issue 4, September 1994
- Qwest USWTR 77359 DIGIPAC[®] Service Interface Specifications For Public Packet Switching Network, Issue E, May 1994

[®] PulseLink is a registered trademark of BellSouth

[®] INFOPATH is a registered service mark of NYNEX.

SM MicroLink II is a registered service mark of Southwestern Bell Telephone.

[®] DIGIPAC is a registered service mark of Qwest Corporation.

2.2 Category 2, Type B - X.75 Packet Switched BSA (1002)


Service Description

The Type B Packet Switched BSA provides an ESP with X.75 access to the BOC packet switching network. The X.75 interface conforms to Recommendation X.75 of the International Telecommunication Union Telecommunication Standardization Sector (ITU-TS) (formerly the International Telegraph and Telephone Consultative Committee [CCITT]).

X.75 includes physical, link and packet level procedures. At the physical level data signaling rates of 9.6 kbps are supported over analog or digital facilities. Speeds of 56 kbps are supported over digital facilities only. The link level protocol supported at the interface is Link Access Protocol Balanced (LAPB). The main functions of the link level protocol are to ensure that the packets cross the network interface essentially error free and reach their destination in a correctly transmitted sequence. The network level access protocol provides the procedures required to set up, maintain and clear virtual calls.

Generic Name of BSA	Regional Company BSA Name
Category 2, Type B - X.75 Packet Switched BSA	AM - Packet Switched Network Service (X.75) BA - Public Data Network: X.75 BS - PulseLink® Packet Switching - X.75 NX - INFOPATH® Packet Switching Service PB - Public Packet Switching (X.75) SWB - Packet Switched - MicroLink II SM (X.75 Version) Qwest - Packet Switching (X.75)

Packet Switching BSA



® PulseLink is a registered trademark of BellSouth.
 ® INFOPATH is a registered service mark of NYNEX.
 SM MicroLink II is a registered service mark of Southwestern Bell Telephone.
 UPDATED 1/31/10

Alternatives

An alternative is an item that must be selected for the BSA to be technically meaningful. Alternative items may be available from some or all of the Local Exchange Carriers (LECs). Refer to the individual LEC tariff reference diskette for the reference information where LEC defined alternatives may be found. Examples of potential alternatives may be: Logical Channel, Flow Control Parameters, and Multiple Network Addresses.

Signaling

Signaling arrangements extend alerting information on metallic or fiber facilities from one customer premises location to another customer premises location. Dial (circuit-switched) access provides low- to moderate-throughput Public Packet Switched Network (PPSN) access through the voice telephone network. With dial-in access, a customer terminal and modem are attached to the Public Switched Telephone Network (PSTN) loop. The customer dials a North American Numbering Plan (NANP) address and the PSTN routes the call to a PPSN dial-up port. The PPSN answers the call with a modem supporting one of several modem protocols.

With dial-out access, a call is routed to a PPSN interface supporting dial-out service. At this interface, the access concentrator obtains the NANP address and uses the ITU-TS (formerly CCITT) V.25 calling procedures to instruct the PPSN modem to establish a physical connection with the customer via the PSTN.

Dedicated (nonswitched) access provides the customer with continuously available interfaces to the PPSN.

Transmission

The subject of transmission covers a broad range of performance considerations related to the physical facilities that compose network architecture. Transmission parameters are designed to provide objective transmission performance characteristics, as perceived by the end user and LEC, between the points of termination. Transmission parameters are defined for each Network Interface (see below) supporting this BSA. These parameters are defined in the reference documentation.

Network Interface

The electrical and physical interface with the LEC is described by a Network Channel Interface (NCI) code for each end user termination and each service provider termination. NCI codes are provided to aid the user in understanding the relationship of the network interface to the electrical or optical characteristics of the interface. NCI codes have four basic components: (1) number of conductors (wire or fibers), (2) protocol code, (3) nominal reference impedance code, and (4) any applicable protocol options.

References

- GR-301 Public Packet Switched Network Generic Requirements (PPSNGR) (replaces TR-TSY-301, Issue 2), Issue 2, December 1997
- TR-NPL-000011 Asynchronous Terminal and Host Interface Reference, Issue 1, March 1985 [No longer listed.]
- Ameritech TR-NPL-000001 Public Packet Services Technical Interface Specifications, Issue 2, September 1988
- Ameritech TR-NPL-000003 Technical Interface Specifications for Asynchronous Service, Issue 2, May 1988
- Ameritech TR-NPL-000007 Digital Service Interface Specifications, Type 1, Issue B, December 1988
- Ameritech TR-NPL-000016 Technical Interface Specifications for X.75 Service, Issue 2, May 1988

- Bell Atlantic TR 72211 Interface Specification For The Bell Atlantic Public Data Network, Issue C, December 1991
- BellSouth TR-73515 PulseLink[®] X.75 Interface Specification, Issue B, April 1991
- BellSouth TR-73516 PulseLink[®] Physical Interface Specification, Issue C, September 1991
- NYNEX NTR-74250 INFOPATH[®] Packet Switching Service X.25 Interface Specification, Issue 2, January 1988
- Pacific Bell PUB L-780060-PB Public Packet Switching (PPS) - Technical Interface Specification, Issue 1, August 1989
- Southwestern Bell Telephone Technical Publication TP 76800, MicroLink IISM X.25/X.75 Reference, Issue 4, September 1994
- Qwest USWTR 77359 DIGIPAC[®] Service Interface Specifications For Public Packet Switching Network, Issue E, May 1994

[®] PulseLink is a registered trademark of BellSouth.

[®] INFOPATH is a registered service mark of NYNEX.

SM MicroLink II is a registered service mark of Southwestern Bell Telephone.

[®] DIGIPAC is a registered service mark of Qwest Corporation.